# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12447067

| | | | |
|---|---|---|---|
| Frame | : 284/6TC | Cooling method | : IC411 - TEFC |
| Insulation class | : F | Mounting | : F-1 |
| Duty cycle | : Cont.(S1) | Rotation[1] | : Both (CW and CCW) |
| Ambient temperature | : -20°C to +40°C | Starting method | : Direct On Line |
| Altitude | : 1000 m.a.s.l. | Approx. weight[3] | : 176 kg |
| Protection degree | : IP55 | Moment of inertia (J) | : 0.2153 kgm² |
| Design | : B | | |

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Output [HP] | | 25 | 20 | 20 | 20 | 25 | 25 | 25 |
| Poles | | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Frequency [Hz] | | 60 | 50 | 50 | 50 | 50 | 50 | 50 |
| Rated voltage [V] | | 230/460 | 380 | 400 | 415 | 380 | 400 | 415 |
| Rated current [A] | | 59.0/29.5 | 29.1 | 28.2 | 27.5 | 35.9 | 34.3 | 33.2 |
| L. R. Amperes [A] | | 366/183 | 175 | 189 | 198 | 190 | 189 | 196 |
| LRC [A] | | 6.2x(Code G) | 6.0x(Code G) | 6.7x(Code H) | 7.2x(Code J) | 5.3x(Code F) | 5.5x(Code F) | 5.9x(Code G) |
| No load current [A] | | 22.0/11.0 | 11.0 | 11.7 | 12.4 | 11.0 | 11.7 | 12.4 |
| Rated speed [RPM] | | 1770 | 1470 | 1473 | 1475 | 1455 | 1460 | 1465 |
| Slip [%] | | 1.67 | 2.00 | 1.80 | 1.67 | 3.00 | 2.67 | 2.33 |
| Rated torque [kgfm] | | 10 | 9 | 9 | 9 | 12 | 12 | 12 |
| Locked rotor torque [%] | | 240 | 229 | 250 | 270 | 180 | 200 | 220 |
| Breakdown torque [%] | | 270 | 260 | 300 | 330 | 210 | 240 | 260 |
| Service factor | | 1.25 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 | 1.00 |
| Temperature rise | | 80 K | 80 K | 80 K | 80 K | 105 K | 105 K | 105 K |
| Locked rotor time | | 43s (cold) 24s (hot) | 32s (cold) 18s (hot) | 32s (cold) 18s (hot) | 32s (cold) 18s (hot) | 25s (cold) 14s (hot) | 25s (cold) 14s (hot) | 25s (cold) 14s (hot) |
| Noise level[2] | | 63.0 dB(A) | 61.0 dB(A) | 61.0 dB(A) | 61.0 dB(A) | 61.0 dB(A) | 61.0 dB(A) | 61.0 dB(A) |
| Efficiency (%) | 25% | | | | | | | |
| | 50% | 92.4 | 91.3 | 91.3 | 91.2 | 92.4 | 92.4 | 92.4 |
| | 75% | 93.0 | 92.1 | 92.5 | 92.5 | 91.7 | 92.4 | 92.4 |
| | 100% | 93.6 | 92.1 | 92.6 | 92.7 | 91.0 | 91.7 | 92.4 |
| Power Factor | 25% | | | | | | | |
| | 50% | 0.70 | 0.69 | 0.65 | 0.62 | 0.76 | 0.73 | 0.70 |
| | 75% | 0.80 | 0.80 | 0.78 | 0.75 | 0.84 | 0.82 | 0.80 |
| | 100% | 0.84 | 0.85 | 0.83 | 0.82 | 0.86 | 0.85 | 0.84 |

Losses at normative operating points (speed;torque), in percentage of rated output power

| | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Losses (%) | P1 (0,9;1,0) | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 | 6.8 |
| | P2 (0,5;1,0) | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 | 5.8 |
| | P3 (0,25;1,0) | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 | 5.3 |
| | P4 (0,9;0,5) | 3.1 | 3.1 | 3.1 | 3.1 | 3.1 | 3.1 | 3.1 |
| | P5 (0,5;0,5) | 2.2 | 2.2 | 2.2 | 2.2 | 2.2 | 2.2 | 2.2 |
| | P6 (0,5;0,25) | 1.4 | 1.4 | 1.4 | 1.4 | 1.4 | 1.4 | 1.4 |
| | P7 (0,25;0,25) | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |

| | | Drive end | Non drive end |
|---|---|---|---|
| Bearing type | : | 6311 C3 | 6211 C3 |
| Sealing | : | V'Ring | V'Ring |
| Lubrication interval | : | 20000 h | 20000 h |
| Lubricant amount | : | 18 g | 11 g |
| Lubricant type | : | Mobil Polyrex EM | |

Foundation loads

Max. traction : 369 kgf

Max. compression : 552 kgf

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 1 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# DATA SHEET

## Three Phase Induction Motor - Squirrel Cage

Customer :

Notes
USABLE @208V 65.2A SF 1.15 SFA 75.0A

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 2 / 9 | |


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : |

| | | | |
|---|---|---|---|
| Product line | : W22 NEMA Premium Efficiency Three-Phase | Product code : | 12447067 |




| | | | |
|---|---|---|---|
| Performance | : 230/460 V 60 Hz 4P | | |
| Rated current | : 59.0/29.5 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 6.2 | Duty cycle | : Cont.(S1) |
| Rated torque | : 10 kgfm | Insulation class | : F |
| Locked rotor torque | : 240 % | Service factor | : 1.25 |
| Breakdown torque | : 270 % | Temperature rise | : 80 K |
| Rated speed | : 1770 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 3 / 9 | |


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : |

| | | | |
|---|---|---|---|
| Product line | : W22 NEMA Premium Efficiency Three-Phase | Product code : | 12447067 |




| | |
|---|---|
| Performance | : 380 V 50 Hz 4P IE3 |

| | | | |
|---|---|---|---|
| Rated current | : 29.1 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 6.0 | Duty cycle | : Cont.(S1) |
| Rated torque | : 9 kgfm | Insulation class | : F |
| Locked rotor torque | : 229 % | Service factor | : 1.00 |
| Breakdown torque | : 260 % | Temperature rise | : 80 K |
| Rated speed | : 1470 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 4 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12447067




| | | | |
|---|---|---|---|
| Performance | : 400 V 50 Hz 4P IE3 | | |
| Rated current | : 28.2 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 6.7 | Duty cycle | : Cont.(S1) |
| Rated torque | : 9 kgfm | Insulation class | : F |
| Locked rotor torque | : 250 % | Service factor | : 1.00 |
| Breakdown torque | : 300 % | Temperature rise | : 80 K |
| Rated speed | : 1473 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 5 / 9 | |


This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : |

| | | | |
|---|---|---|---|
| Product line | : W22 NEMA Premium Efficiency Three-Phase | Product code : | 12447067 |




| | |
|---|---|
| Performance | : 415 V 50 Hz 4P IE3 |

| | | | |
|---|---|---|---|
| Rated current | : 27.5 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 7.2 | Duty cycle | : Cont.(S1) |
| Rated torque | : 9 kgfm | Insulation class | : F |
| Locked rotor torque | : 270 % | Service factor | : 1.00 |
| Breakdown torque | : 330 % | Temperature rise | : 80 K |
| Rated speed | : 1475 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 6 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12447067




| | | | |
|---|---|---|---|
| Performance | : 380 V 50 Hz 4P IE1 | | |
| Rated current | : 35.9 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 5.3 | Duty cycle | : Cont.(S1) |
| Rated torque | : 12 kgfm | Insulation class | : F |
| Locked rotor torque | : 180 % | Service factor | : 1.00 |
| Breakdown torque | : 210 % | Temperature rise | : 105 K |
| Rated speed | : 1455 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 7 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12447067




| | | | |
|---|---|---|---|
| Performance | : 400 V 50 Hz 4P IE2 | | |
| Rated current | : 34.3 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 5.5 | Duty cycle | : Cont.(S1) |
| Rated torque | : 12 kgfm | Insulation class | : F |
| Locked rotor torque | : 200 % | Service factor | : 1.00 |
| Breakdown torque | : 240 % | Temperature rise | : 105 K |
| Rated speed | : 1460 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 8 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


# LOAD PERFORMANCE CURVE

## Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 NEMA Premium Efficiency Three-Phase

Product code : 12447067




| Performance | : 415 V 50 Hz 4P IE2 | | |
|---|---|---|---|
| Rated current | : 33.2 A | Moment of inertia (J) | : 0.2153 kgm² |
| LRC | : 5.9 | Duty cycle | : Cont.(S1) |
| Rated torque | : 12 kgfm | Insulation class | : F |
| Locked rotor torque | : 220 % | Service factor | : 1.00 |
| Breakdown torque | : 260 % | Temperature rise | : 105 K |
| Rated speed | : 1465 rpm | Design | : B |

| Rev. | Changes Summary | Performed | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | | | | |
| Checked by | | | Page | Revision |
| Date | 23/09/2026 | | 9 / 9 | |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice