DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W22 - Nema Premium Efficiency (Derating)

Frame	: 364/5TC	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: B34R(D)
Duty cycle	: S1	Rotation	: Both
Ambient temperature	: -20 °C to +40 °C	Starting method	: Direct On Line
Altitude	: 1000 m	Approx. weight	: 417 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.9798 kgm²
Design	: B		

Output		75 HP (55 kW)	75 HP (55 kW)
Poles		4	4
Frequency		60 Hz	50 Hz
Rated voltage		230/460 V	380 V
Rated current		174/87.2 A	106 A
L. R. Amperes		1116/558 A	541 A
LRC		6.4 Code G	5.1 Code E
No load current		66.0/33.0 A	33.0 A
Rated speed		1780 rpm	1470 rpm
Slip		1.11 %	2.00 %
Rated torque		30.6 kgfm	37.0 kgfm
Locked rotor torque		240 %	170 %
Breakdown torque		260 %	200 %
Service factor		1.25	1.00
Temperature rise		80 K	105 K
Noise level		67 dB(A)	63 dB(A)
Locked rotor time		14 s (hot) 25 s (cold)	10 s (hot) 18 s (cold)
Efficiency (%)	50%	94.5	94.5
	75%	95.0	94.1
	100%	95.4	93.6
Power Factor	Start	0.40	0.40
	50%	0.68	0.75
	75%	0.78	0.82
	100%	0.83	0.84
Losses at normative operating points (speed;torque), in percentage of rated output power			
P1 (0,9;1,0)		4.71	4.71
P2 (0,5;1,0)		3.78	3.78
P3 (0,25;1,0)		3.48	3.48
P4 (0,9;0,5)		2.43	2.43
P5 (0,5;0,5)		1.60	1.60
P6 (0,5;0,25)		1.10	1.10
P7 (0,25;0,25)		0.71	0.71

	Drive end	Non drive end
Bearing type	6314-C3	6314-C3
Lubrication interval	12000 h	12000 h
Lubricant amount	27 g	27 g
Lubricant type	MOBIL POLYREX EM	

Foundation loads
Max. traction : 674 kgf
Max. compression : 1091 kgf

Notes:

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/12


Performed by				
Checked by			Page	Revision
Date	2026/11/12		1/3	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W22 - Nema Premium Efficiency (Derating)



Performance	: 75 HP (55 kW) 208/230/460V 60Hz 4P 364/5TC

Rated current	: 186/174/87.2 A	Moment of inertia (J)	: 0.9798 kgm²
LRC	: 6.4 Code G	Duty cycle	: Cont.(S1)
Rated torque	: 30.6 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 260 %	Temperature rise	: 80 K
Rated speed	: 1780 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/12


Performed by				
Checked by			Page	Revision
Date	2026/11/12		2/3	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W22 - Nema Premium Efficiency (Derating)



Performance	: 75 HP (55 kW) 380V 50Hz 4P 364/5TC

Rated current	: 106 A	Moment of inertia (J)	: 0.9798 kgm²
LRC	: 5.1 Code E	Duty cycle	: Cont.(S1)
Rated torque	: 37.0 kgfm	Insulation class	: F
Locked rotor torque	: 170 %	Service factor	: 1.00
Breakdown torque	: 200 %	Temperature rise	: 105 K
Rated speed	: 1470 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/12

Performed by				
Checked by			Page	Revision
Date	2026/11/12		3/3	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.