DATA SHEET
Three Phase Induction Motor - Squirrel Cage

Customer	: V.J. PAMENSKY CANADA INC.
Product line	: W01 - ODP - Nema Premium Efficiency - Derating Product code : 12687685

Frame	: 254/6T	Cooling method	: IC01 - ODP
Insulation class	: F	Mounting	: F-1/B3R(D)
Duty cycle	: S1	Rotation¹	: Both
Ambient temperature	: -20 °C to +40 °C	Starting method	: Direct On Line
Altitude	: 3280 ft	Approx. weight³	: 189 lb
Protection degree	: IP21	Moment of inertia (J)	: 1.82 sq.ft.lb
Design	: B		

Output		15 HP (11 kW)	15 HP (11 kW)	15 HP (11 kW)
Poles		4	4	4
Frequency		60 Hz	50 Hz	50 Hz
Rated voltage		230/460 V	190/380 V	220/415 V
Rated current		37.2/18.6 A	43.8/21.9 A	39.4/20.9 A
L. R. Amperes		249/125 A	237/118 A	248/132 A
LRC		6.7	5.4	6.3
No load current		19.0/9.50 A	17.3/8.67 A	19.8/10.5 A
Rated speed		1775 rpm	1465 rpm	1470 rpm
Slip		1.39 %	2.33 %	2.00 %
Rated torque		43.8 ft.lb	53.0 ft.lb	52.9 ft.lb
Locked rotor torque		240 %	170 %	210 %
Pull up torque		200 %	145 %	175 %
Breakdown torque		300 %	220 %	270 %
Service factor		1.15	1.15	1.15
Temperature rise		80 K	80 K	80 K
Noise level²		64.0 dB(A)	62.0 dB(A)	62.0 dB(A)
Locked rotor time (hot)		17 s	0 s	0 s
Locked rotor time (cold)		31 s	0 s	0 s
Efficiency (%)	50%	91.7	91.3	90.3
	75%	92.4	91.0	90.9
	100%	93.0	89.7	90.3
Power Factor	50%	0.62	0.71	0.62
	75%	0.73	0.81	0.75
	100%	0.80	0.85	0.81

	Drive end	Non drive end
Bearing type	6309-Z-C3	6208-Z-C3
Lubrication interval	20000 h	20000 h
Lubricant amount	13 g	8 g
Lubricant type	MOBIL POLYREX EM	

Foundation loads	
Max. traction	:
Max. compression	:
Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date

Performed by	farazq		1851560909	
Checked by	AUTOMATICO		Page	Rev.
Date	22/05/2026		1 / 2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

DATA SHEET
Three Phase Induction Motor - Squirrel Cage

Customer : V.J. PAMENSKY CANADA INC.

Product line : W01 - ODP - Nema Premium Efficiency - Derating Product code : 12687685

Thermal protection ID	Application	Type	Quantity	Sensing Temperature

Notes
USABLE @208V 41.1A SF 1.00 SFA 41.1A

Standards				
	Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
	Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
	Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Rev.	Checked	Date

Performed by	farazq		1851560909	
Checked by	AUTOMATICO		Page	Rev.
Date	22/05/2026		2 / 2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.