DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : Rolled Steel Premium Efficiency Three-Phase

Product code : 15942412

Frame	: W56C	Locked rotor time	: 36s (cold) 20s (hot)
Output	: 0.5 HP (0.37 kW)	Temperature rise	: 80 K
Poles	: 4	Duty cycle	: Cont.(S1)
Frequency	: 60 Hz	Ambient temperature	: -20°C to +40°C
Rated voltage	: 208-230/460 V	Altitude	: 1000 m.a.s.l.
Rated current	: 1.72-1.56/0.778 A	Protection degree	: IP55
L. R. Amperes	: 11.0-9.96/4.98 A	Cooling method	: IC411 - TEFC
LRC	: 6.4x(Code J)	Mounting	: W-12
No load current	: 0.855-0.992/0.496 A	Rotation[1]	: Both (CW and CCW)
Rated speed	: 1730 rpm	Noise level[2]	: 50.0 dB(A)
Slip	: 3.89 %	Vibration	: A
Rated torque	: 0 kgfm	Starting method	: Direct On Line
Locked rotor torque	: 229 %	Approx. weight[3]	: 9.5 kg
Breakdown torque	: 310 %		: 207N (ISO 12944 - C2)
Insulation class	: F		: Munsell N 1 - Matte
Service factor	: 1.15		
Moment of inertia (J)	: 0.0022 kgm²		

Output	50%	75%	100%
Efficiency (%)	74.0	77.0	78.5
Power Factor	0.54	0.67	0.76

Foundation loads

Max. traction	: 15 kgf
Max. compression	: 25 kgf

		Drive end	Non drive end
Bearing type	:	6203 ZZ	6202 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	Mobil Polyrex EM	

Notes
USABLE @208V SF 1.00

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight subject to changes after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	29/09/2026		1 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: Rolled Steel Premium Efficiency Three-Phase	Product code :	15942412



Performance	: 208-230/460 V 60 Hz 4P		
Rated current	: 1.72-1.56/0.778 A	Moment of inertia (J)	: 0.0022 kgm²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 0 kgfm	Insulation class	: F
Locked rotor torque	: 229 %	Service factor	:
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 1730 rpm		

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	29/09/2026		2 / 2	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice