DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Special Motor
Product code	: 11165996

Frame	: 404/5TS
Output	: 100 HP (75 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 230/460 V
Rated current	: 224/112 A
L. R. Amperes	: 1456/728 A
LRC	: 6.5
No load current	: 52.0/26.0 A
Rated speed	: 3545 rpm
Slip	: 1.53 %
Rated torque	: 20.5 kgfm
Locked rotor torque	: 240 %
Pull up torque	: 160 %
Breakdown torque	: 260 %
Insulation class	: F
Service factor	: 1.25
Moment of inertia (J)	: 0.5561 kgm²

Locked rotor time	: 14 s (hot) 25 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: B3R(D)
Rotation[1]	: Both
Noise level[2]	: 79 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 503 kg
Color	: RAL 5009
Design	: B

Output	Start	50%	75%	100%
Efficiency (%)	-	93.0	94.1	94.1
Power Factor	0.39	0.83	0.88	0.89

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6314-C3	6314-C3
Lubrication interval	4000 h	4000 h
Lubrication amount	27 g	27 g
Lubrication type	MOBIL POLYREX EM	

Notes:

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				17/03/2022


Performed by	dmendes		77757/2022	
Checked by	AUTOMATICO		Page	Revision
Date	17/03/2022		1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 11165996



Performance	: 100 HP (75 kW) 230/460/208V 60Hz 2P 404/5TS

Rated current	: 224/112/243 A	Moment of inertia (J)	: 0.5561 kgm²
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 20.5 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 260 %	Temperature rise	: 80 K
Rated speed	: 3545 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date
				17/03/2022

Performed by	dmendes		77757/2022	
Checked by	AUTOMATICO		Page	Revision
Date	17/03/2022		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.