DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : Special Motor
Product code : 14189588

Frame	: 324/6JM
Output	: 60 HP (45 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 56.1 A
L. R. Amperes	: 438 A
LRC	: 7.8 Code J
No load current	: 18.5 A
Rated speed	: 3565 rpm
Slip	: 0.97 %
Rated torque	: 12.2 kgfm
Locked rotor torque	: 290 %
Pull up torque	: 245 %
Breakdown torque	: 300 %
Insulation class	: F
Service factor	: 1.15
Moment of inertia (J)	: 0.2115 kgm²

Locked rotor time	: 13 s (hot) 23 s (cold)
Temperature rise[4]	: 80 K (SF 1.00)
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: B34R(D)
Rotation[1]	: Both
Noise level[2]	: 78 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 265 kg
Design	: A

Output	Start	50%	75%	100%
Efficiency (%)	-	92.4	93.6	93.6
Power Factor	0.00	0.73	0.82	0.86

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6312-C3	6212-C3
Lubrication interval	12000 h	15000 h
Lubrication amount	21 g	13 g
Lubricant type	MOBIL POLYREX EM	

Notes:
JM JET PUMP - W22 - NEMA Premium Efficiency

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
0.00	0.00	0.00	0.00	0.00	0.00	0.00

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				18/05/2023


Performed by	roselaineb	214744/2017	
Checked by	sheylane	Page	Revision
Date	18/05/2023	1/2	2

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 14189588



Performance	: 60 HP (45 kW) 575V 60Hz 2P 324/6JM

Rated current	: 56.1 A	Moment of inertia (J)	: 0.2115 kgm²
LRC	: 7.8 Code J	Duty cycle	: Cont.(S1)
Rated torque	: 12.2 kgfm	Insulation class	: F
Locked rotor torque	: 290 %	Service factor	: 1.15
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 3565 rpm	Design	: A

Rev.	Changes Summary	Performed	Checked	Date
				18/05/2023

Performed by	roselaineb		214744/2017	
Checked by	sheylane		Page	Revision
Date	18/05/2023		2/2	2

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.