DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Special Motor
Product code	: 15597826

Frame	: W56J
Output	: 0.5 HP (0.37 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 230/460 V
Rated current	: 1.76/0.879 A
L. R. Amperes	: 12.8/6.42 A
LRC	: 7.3 Code M
No load current	: 1.20/0.600 A
Rated speed	: 3450 rpm
Slip	: 4.17 %
Rated torque	: 0.105 kgfm
Locked rotor torque	: 370 %
Pull up torque	: 315 %
Breakdown torque	: 400 %
Insulation class	: F
Service factor	: 1.60
Moment of inertia (J)	: 0.0006 kgm²

Locked rotor time	: 24 s (hot) 43 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP21
Cooling method	: IC01 - ODP
Mounting	: F-1/B14R(D)
Rotation[1]	: Counter clockwise
Noise level[2]	: 62 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 6.7 kg

Output	Start	50%	75%	100%
Efficiency (%)	-	62.0	68.0	73.4
Power Factor	0.79	0.53	0.65	0.72

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6203-2RS	6202-2RS
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Notes:

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				23/06/2026


Performed by	linsj		277606/2020	
Checked by	AUTOMATICO		Page	Revision
Date	23/06/2026		1/2	3

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 15597826



Performance	: 0.5 HP (0.37 kW) 230/460V 60Hz 2P W56J

Rated current	: 1.76/0.879 A	Moment of inertia (J)	: 0.0006 kgm²
LRC	: 7.3 Code M	Duty cycle	: Cont.(S1)
Rated torque	: 0.105 kgfm	Insulation class	: F
Locked rotor torque	: 370 %	Service factor	: 1.60
Breakdown torque	: 400 %	Temperature rise	: 80 K
Rated speed	: 3450 rpm		

Rev.	Changes Summary	Performed	Checked	Date
				23/06/2026

Performed by	linsj		277606/2020	
Checked by	AUTOMATICO		Page	Revision
Date	23/06/2026		2/2	3

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.