# DATA SHEET
## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : V.J. PAMENSKY CANADA INC. |
| Product line | : W01 - TEFC - Premium Efficiency (DOE) Jet Pump - Forma J |

| | | | |
|---|---|---|---|
| Frame | : W56J | Locked rotor time | : 22 s (hot) 40 s (cold) |
| Output | : 0.33 HP (0.25 kW) | Temperature rise | : 80 K |
| Poles | : 4 | Duty cycle | : S1 |
| Frequency | : 60 Hz | Ambient temperature | : -20 °C to +40 °C |
| Rated voltage | : 575 V | Altitude | : 3280 ft |
| Rated current | : 0.499 A | Protection degree | : IP55 |
| L. R. Amperes | : 3.10 A | Cooling method | : IC411 - TEFC |
| LRC | : 6.2 | Mounting | : W-6/V18R(D) |
| No load current | : 0.380 A | Rotation[1] | : Counter clockwise |
| Rated speed | : 1740 rpm | Noise level[2] | : 50.0 dB(A) |
| Slip | : 3.33 % | Vibration class | : A |
| Rated torque | : 0.984 ft.lb | Starting method | : Direct On Line |
| Locked rotor torque | : 260 % | Approx. weight[3] | : 18.3 lb |
| Pull up torque | : 220 % | Color | : PRIMER ONLY |
| Breakdown torque | : 350 % | | |
| Insulation class | : F | | |
| Service factor | : 1.15 | | |
| Moment of inertia (J) | : 0.0356 sq.ft.lb | | |

| Output | 50% | 75% | 100% |
|---|---|---|---|
| Efficiency (%) | 66.0 | 72.0 | 74.0 |
| Power Factor | 0.46 | 0.58 | 0.68 |

| | Drive end | Non drive end |
|---|---|---|
| Bearing type #1 | 6203-2RS | 6202-2RS |
| Bearing type #2 | - | - |
| Lubrication interval | - | - |
| Lubricant amount #1 | - | - |
| Lubricant amount #2 | - | - |
| Lubricant type | MOBIL POLYREX EM | |

| | |
|---|---|
| Load type | : - |
| Load torque | : - |
| Load inertia (J=GD²/4) | : - |
| Foundation loads | |
| Max. traction | : 110 N |
| Max. compression | : 191 N |

Notes
See notes on page 2.

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

| Rev. | Changes Summary | Rev. | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | farazq | | 1867025839 | |
| Checked by | AUTOMATICO | | Page | Rev. |
| Date | 29/06/2026 | | 1 / 2 | 0 |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

# DATA SHEET
## Three Phase Induction Motor - Squirrel Cage

| | |
|---|---|
| Customer | : V.J. PAMENSKY CANADA INC. |
| Product line | : W01 - TEFC - Premium Efficiency (DOE) Jet Pump - Forma J |

| Thermal protection ID | Application | Type | Quantity | Sensing Temperature |
|---|---|---|---|---|

Notes

| Standards | | | | |
|---|---|---|---|---|
| | Specification | : MG1 - Part 10 | Vibration | : MG1 - Part 7 |
| | Test | : MG1 - Part 12 | Tolerance | : MG1 - Part 12 |
| | Noise | : MG1 - Part 9 | | |

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +3dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

| Rev. | Changes Summary | Rev. | Checked | Date |
|---|---|---|---|---|
| | | | | |

| | | | | |
|---|---|---|---|---|
| Performed by | farazq | | 1867025839 | |
| Checked by | AUTOMATICO | | Page | Rev. |
| Date | 29/06/2026 | | 2 / 2 | 0 |

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.