DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: Special Motor
Product code	: 13641595

Frame	: W56J
Output	: 0.5 HP (0.37 kW)
Poles	: 4
Frequency	: 60 Hz
Rated voltage	: 230-208/460 V
Rated current	: 1.56-1.72/0.778 A
L. R. Amperes	: 11.0-4.98 A
LRC	: 6.4 Code J
No load current	: 0-0.496 A
Rated speed	: 1730 rpm
Slip	: 3.89 %
Rated torque	: 0.210 kgfm
Locked rotor torque	: 230 %
Pull up torque	: 195 %
Breakdown torque	: 310 %
Insulation class	: F
Service factor	: 1.25
Moment of inertia (J)	: 0.0022 kgm²

Locked rotor time	: 20 s (hot) 36 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: F-1/B14R(D)
Rotation[1]	: Counter clockwise
Noise level[2]	: 50 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 9.5 kg

Output	Start	50%	75%	100%
Efficiency (%)	-	74.0	77.0	78.5
Power Factor	0.77	0.54	0.67	0.76

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6203-2RS	6202-2RS
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Notes:

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
0.00	0.00	0.00	0.00	0.00	0.00	0.00

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				16/02/2021


Performed by	wendy	109028/2016	
Checked by	esalazar	Page	Revision
Date	12/02/2021	1/2	3

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: Special Motor
Product code	: 13641595



Performance	: 0.5 HP (0.37 kW) 230/208/460V 60Hz 4P W56J

Rated current	: 1.56/1.72/0.778 A	Moment of inertia (J)	: 0.0022 kgm²
LRC	: 6.4 Code J	Duty cycle	: Cont.(S1)
Rated torque	: 0.210 kgfm	Insulation class	: F
Locked rotor torque	: 230 %	Service factor	: 1.25
Breakdown torque	: 310 %	Temperature rise	: 80 K
Rated speed	: 1730 rpm		

Rev.	Changes Summary	Performed	Checked	Date
				16/02/2021

Performed by	wendy		109028/2016	
Checked by	esalazar		Page	Revision
Date	12/02/2021		2/2	3

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.