DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: W01 - TEFC - Premium Efficiency (DOE) Jet Pump - Forma J
Product code	: 15942858

Frame	: W56J
Output	: 0.5 HP (0.37 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 575 V
Rated current	: 0.627 A
L. R. Amperes	: 4.83 A
LRC	: 7.7 Code L
No load current	: 0.334 A
Rated speed	: 3435 rpm
Slip	: 4.58 %
Rated torque	: 0.106 kgfm
Locked rotor torque	: 330 %
Pull up torque	: 280 %
Breakdown torque	: 360 %
Insulation class	: F
Service factor	: 1.15
Moment of inertia (J)	: 0.0008 kgm²

Locked rotor time	: 18 s (hot) 32 s (cold)
Temperature rise[4]	: 80 K
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: W-6/V18R(D)
Rotation[1]	: Counter clockwise
Noise level[2]	: 65 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 7.9 kg
Design	:

Output	Start	50%	75%	100%
Efficiency (%)	-	68.0	72.0	74.0
Power Factor	0.77	0.64	0.75	0.8

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6203-2RS	6202-2RS
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	MOBIL POLYREX EM	

Notes:

Losses at normative operating points (speed;torque), in percentage of rated output power

P1 (0,9;1,0)	P2 (0,5;1,0)	P3 (0,25;1,0)	P4 (0,9;0,5)	P5 (0,5;0,5)	P6 (0,5;0,25)	P7 (0,25;0,25)
0.00	0.00	0.00	0.00	0.00	0.00	0.00

Standards

Specification	: MG1 - Part 10	Vibration	: MG1 - Part 7
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/27


Performed by				
Checked by			Page	Revision
Date	2026/10/27		1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W01 - TEFC - Premium Efficiency (DOE) Jet Pump - Forma J
Product code	: 15942858



Performance	: 0.5 HP (0.37 kW) 575V 60Hz 2P W56J

Rated current	: 0.627 A	Moment of inertia (J)	: 0.0008 kgm²
LRC	: 7.7 Code L	Duty cycle	: Cont.(S1)
Rated torque	: 0.106 kgfm	Insulation class	: F
Locked rotor torque	: 330 %	Service factor	: 1.15
Breakdown torque	: 360 %	Temperature rise	: 80 K
Rated speed	: 3435 rpm		

Rev.	Changes Summary	Performed	Checked	Date
				2026/10/27

Performed by				
Checked by			Page	Revision
Date	2026/10/27		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.