DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13016495

Frame	: 215HP	Cooling method	: IC411 - TEFC
Insulation class	: F	Mounting	: W-6
Duty cycle	: Cont.(S1)	Rotation¹	: Both (CW and CCW)
Ambient temperature	: -20°C to +40°C	Starting method	: Direct On Line
Altitude	: 1000 m.a.s.l.	Approx. weight³	: 78.0 kg
Protection degree	: IP55	Moment of inertia (J)	: 0.0636 kgm²
Design	: B		

Output [HP]		10	7.5	7.5	7.5	10	10	10
Poles		4	4	4	4	4	4	4
Frequency [Hz]		60	50	50	50	50	50	50
Rated voltage [V]		230/460	380	400	415	380	400	415
Rated current [A]		25.3/12.7	11.5	11.4	11.3	15.2	14.4	14.1
L. R. Amperes [A]		162/81.1	86.2	91.5	96.1	90.9	93.6	98.8
LRC [A]		6.4x(Code H)	7.5x(Code J)	8.0x(Code K)	8.5x(Code L)	6.0x(Code G)	6.5x(Code H)	7.0x(Code H)
No load current [A]		11.6/5.80	5.60	6.00	6.35	5.60	6.00	6.35
Rated speed [RPM]		1765	1470	1475	1475	1450	1455	1460
Slip [%]		1.94	2.00	1.67	1.67	3.33	3.00	2.67
Rated torque [kgfm]		4	3	3	3	5	4	4
Locked rotor torque [%]		240	200	240	260	165	180	190
Breakdown torque [%]		295	300	340	360	220	250	270
Service factor		1.25	1.15	1.15	1.15	1.15	1.15	1.15
Temperature rise		80 K	80 K	80 K	80 K	80 K	80 K	80 K
Locked rotor time		30s (cold) 17s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	25s (cold) 14s (hot)	0s (cold) 0s (hot)
Noise level²		58.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)	56.0 dB(A)
Efficiency (%)	25%							
	50%	91.0	90.0	89.2	88.7	88.0	90.3	90.3
	75%	91.7	90.0	89.9	89.8	88.5	90.2	90.2
	100%	91.7	89.8	90.1	90.3	88.5	89.5	90.2
Power Factor	25%							
	50%	0.65	0.61	0.57	0.53	0.72	0.68	0.64
	75%	0.76	0.74	0.70	0.67	0.81	0.79	0.76
	100%	0.81	0.81	0.77	0.75	0.85	0.84	0.82

Losses at normative operating points (speed;torque), in percentage of rated output power

Losses (%)	P1 (0,9;1,0)	8.8	11.0	10.7	10.4	12.6	11.4	10.5
	P2 (0,5;1,0)	7.3	9.2	8.9	8.7	10.5	9.5	8.8
	P3 (0,25;1,0)	7.1	8.9	8.6	8.4	10.2	9.2	8.5
	P4 (0,9;0,5)	4.6	5.7	5.6	5.4	6.6	5.9	5.5
	P5 (0,5;0,5)	3.2	4.0	3.8	3.8	4.5	4.1	3.8
	P6 (0,5;0,25)	2.2	2.8	2.7	2.6	3.2	2.9	2.7
	P7 (0,25;0,25)	1.5	1.9	1.9	1.8	2.2	2.0	1.9

		Drive end	Non drive end
Bearing type	:	6309 ZZ	6207 ZZ
Sealing	:	V'Ring	V'Ring
Lubrication interval	:	-	-
Lubricant amount	:	-	-
Lubricant type	:	00088	

Foundation loads

Max. traction : 0 kgf

Max. compression : 0 kgf

This revision replaces and cancel the previous one, which must be eliminated.
(1) Looking the motor from the shaft end.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG-1.

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/10/2026		1 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

DATA SHEET

Three Phase Induction Motor - Squirrel Cage

Customer :

Notes
USABLE @208V 27.4A SF 1.15 SFA 31.5A

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/10/2026		2 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13016495



Performance	: 230/460 V 60 Hz 4P		
Rated current	: 25.3/12.7 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 6.4	Duty cycle	: Cont.(S1)
Rated torque	: 4 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.25
Breakdown torque	: 295 %	Temperature rise	: 80 K
Rated speed	: 1765 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	14/10/2026		3 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: W22 P Base NEMA Premium Efficiency Three-Phase	Product code :	13016495



Performance	: 380 V 50 Hz 4P IE3		
Rated current	: 11.5 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 7.5	Duty cycle	: Cont.(S1)
Rated torque	: 3 kgfm	Insulation class	: F
Locked rotor torque	: 200 %	Service factor	: 1.15
Breakdown torque	: 300 %	Temperature rise	: 80 K
Rated speed	: 1470 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/10/2026		4 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13016495



Performance	: 400 V 50 Hz 4P IE3		
Rated current	: 11.4 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 8.0	Duty cycle	: Cont.(S1)
Rated torque	: 3 kgfm	Insulation class	: F
Locked rotor torque	: 240 %	Service factor	: 1.15
Breakdown torque	: 340 %	Temperature rise	: 80 K
Rated speed	: 1475 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	14/10/2026		5 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: W22 P Base NEMA Premium Efficiency Three-Phase	Product code :	13016495



Performance	: 415 V 50 Hz 4P IE3		
Rated current	: 11.3 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 8.5	Duty cycle	: Cont.(S1)
Rated torque	: 3 kgfm	Insulation class	: F
Locked rotor torque	: 260 %	Service factor	: 1.15
Breakdown torque	: 360 %	Temperature rise	: 80 K
Rated speed	: 1475 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	14/10/2026		6 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: W22 P Base NEMA Premium Efficiency Three-Phase	Product code :	13016495



Performance	: 380 V 50 Hz 4P IE1		
Rated current	: 15.2 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 6.0	Duty cycle	: Cont.(S1)
Rated torque	: 5 kgfm	Insulation class	: F
Locked rotor torque	: 165 %	Service factor	: 1.15
Breakdown torque	: 220 %	Temperature rise	: 80 K
Rated speed	: 1450 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date


Performed by				
Checked by			Page	Revision
Date	14/10/2026		7 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice

LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer	:		
Product line	: W22 P Base NEMA Premium Efficiency Three-Phase	Product code :	13016495



Performance	: 400 V 50 Hz 4P IE2		
Rated current	: 14.4 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 6.5	Duty cycle	: Cont.(S1)
Rated torque	: 4 kgfm	Insulation class	: F
Locked rotor torque	: 180 %	Service factor	: 1.15
Breakdown torque	: 250 %	Temperature rise	: 80 K
Rated speed	: 1455 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/10/2026		8 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice


LOAD PERFORMANCE CURVE

Three Phase Induction Motor - Squirrel Cage

Customer :

Product line : W22 P Base NEMA Premium Efficiency Three-Phase

Product code : 13016495



Performance	: 415 V 50 Hz 4P IE2

Rated current	: 14.1 A	Moment of inertia (J)	: 0.0636 kgm²
LRC	: 7.0	Duty cycle	: Cont.(S1)
Rated torque	: 4 kgfm	Insulation class	: F
Locked rotor torque	: 190 %	Service factor	: 1.15
Breakdown torque	: 270 %	Temperature rise	: 80 K
Rated speed	: 1460 rpm	Design	: B

Rev.	Changes Summary	Performed	Checked	Date

Performed by				
Checked by			Page	Revision
Date	14/10/2026		9 / 9	

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.
Subject to change without notice