DATA SHEET

Single Phase Induction Motor - Squirrel Cage

Customer	:

Product line	: W22
Product code	: 18784773

Frame	: 213/5T
Output	: 7.5 HP (5.5 kW)
Poles	: 2
Frequency	: 60 Hz
Rated voltage	: 208-230 V
Rated current	: 30.5-28.8 A
L. R. Amperes	: 207 A
LRC	: 7.2 Code H
No load current	: 5.00 A
Rated speed	: 3500 rpm
Slip	: 2.78 %
Rated torque	: 1.56 kgfm
Locked rotor torque	: 280 %
Pull up torque	: 230 %
Breakdown torque	: 275 %
Insulation class	: F
Service factor	: 1.15
Moment of inertia (J)	: 0.0234 kgm²

Locked rotor time	: 7 s (hot) 13 s (cold)
Duty cycle	: S1
Ambient temperature	: -20 °C to +40 °C
Altitude	: 1000 m.a.s.l
Protection degree	: IP55
Cooling method	: IC411 - TEFC
Mounting	: B3R(D)
Rotation[1]	: Both
Noise level[2]	: 72 dB(A)
Starting method	: Direct On Line
Approx. weight[3]	: 75.0 kg
Design	:

Output	Start	50%	75%	100%
Efficiency (%)	-	78.5	83.0	84.0
Power Factor	0.89	0.96	0.98	0.99

Load type	: -
Load torque	: -
Load inertia (J=GD²/4)	: -

	Drive end	Non drive end
Bearing type	6308-ZZ	6206-ZZ
Lubrication interval	-	-
Lubricant amount	-	-
Lubricant type	POLYUREA BASED GREASE	

Foundation loads	
Max. traction	: -
Max. compression	: -

Notes:

Standards

Specification	: MG1 - Part 10	Vibration	:
Test	: MG1 - Part 12	Tolerance	: MG1 - Part 12
Noise	: MG1 - Part 9		

This revision replaces and cancel the previous one, which must be eliminated..
(1) Looking the motor from the shaft end.
(2) Measured at 1m and with tolerance of +0dB(A).
(3) Approximate weight, subject to be changed after manufacturing process.
(4) At 100% of full load.

These are average values based on tests with sinusoidal power supply, subject to the tolerances stipulated in NEMA MG 1-12.

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/05


Performed by				
Checked by			Page	Revision
Date	2026/11/05		1/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.

LOAD PERFORMANCE CURVE

Single Phase Induction Motor - Squirrel Cage

Customer	:
Product line	: W22
Product code	: 18784773



Performance	: 7.5 HP (5.5 kW) 208/230V 60Hz 2P 213/5T

Rated current	: 30.5/28.8 A	Moment of inertia (J)	: 0.0234 kgm²
LRC	: 7.2 Code H	Duty cycle	: Cont.(S1)
Rated torque	: 1.56 kgfm	Insulation class	: F
Locked rotor torque	: 280 %	Service factor	: 1.15
Breakdown torque	: 275 %	Temperature rise	: 80 K
Rated speed	: 3500 rpm		

Rev.	Changes Summary	Performed	Checked	Date
				2026/11/05

Performed by				
Checked by			Page	Revision
Date	2026/11/05		2/2	0

This document is exclusive property of WEG S/A. Reprinting is not allowed without written authorization of WEG S/A.